

DKM-HD17 Rack Console

Monitor Keyboard Mouse with Flip-up 17.3" Full-HD LCD in a Short-depth Slide-out Drawer

Features

- » Rack console with LCD monitor, keyboard and touchpad mouse.
- » Slide-out rack mount drawer designed for 19 inch racks.
- » Monitor and keyboard take up only 1U rack space.
- » Flip-up 17.3" LCD @ 1920 x 1080 pixels HD resolution.
- » LED backlight LCD panel.
- » Built-in speakers and audio connector.
- » Front bezel control buttons for display adjustment.
- » Only 16" in depth (including drawer handle).
- » Detachable slide rails with adjustable mounting brackets.
- » Choice of PS/2 or USB models.

Single Point Server Management

The DKM-HD17 is a rack-mountable flat panel LCD monitor that occupies only 1 rack unit space. Using a flip-up monitor design, the DKM-HD17 offers a low profile rack mount console for your server. The LCD monitor and keyboard drawer is mounted on slide rails so you can easily pull the unit out of your equipment rack. The LCD monitor flips up for use and folds down for storage. Using an extension bracket that lets you adjust flange to flange distance from 14.5" to 24.5", the DKM-HD17 is designed for shallow-depth cabinets as well as regular equipment racks.

The DKM-HD17 has a LED backlight LCD monitor that offers full HD resolution and 6-bit color display. The LCD's lower power consumption and EMI free technology makes it ideal for industrial applications. And with its native resolution of 1920 x 1080 pixels, you can work more and scroll less, because you can put more information on screen instead of cluttering it with menus and tool bars. An on-screen display (OSD) menu using four front-panel-mounted control buttons let's you adjust the display for optimum viewing.

The DKM-HD17 provides your server with a PS/2 or USB keyboard and touchpad mouse.



DKM-HD17 Rack Console

Technical Specifications

<i>Physical Specifications</i>	
<i>Chassis</i>	1U slide-out rack mount drawer with LCD monitor, keyboard and touch-pad mouse. Rugged metal construction.
<i>Mounting Options</i>	Designed for 19" racks. Mounting brackets extension from 14.5" to 24.5" in depth.
<i>Form Factor</i>	1U rack-mountable.
<i>Electrical and Power</i>	Autosensing AC power supply.
<i>External Controls</i>	Front bezel OSD menu controls for LCD contrast, brightness, image position, color temperature, language, focus. LCD backlight on/off button.
<i>I/O Connectors</i>	D-Sub 15-pin VGA, DVI-D dual link, audio connectors. PS/2 or USB connector for keyboard and mouse.
<i>Dimensions</i>	19.0" (W) x 1.75" (H) x 17.0" (D). Depth includes drawer handle and protrusion of PS/2 model's keyboard/mouse connectors.
<i>Weight</i>	21 lbs. (28 lbs. shipping weight).

<i>Flat Panel LCD Specifications</i>	
<i>Display Type</i>	Active matrix TFT LCD with anti-glare surface treatment.
<i>Display Size</i>	17.3-inch screen (measured diagonally).
<i>Resolution</i>	1920 x 1080 optimum resolution (full HD).
<i>Color Depth</i>	6-bit color depth per RGB channel (262k colors).
<i>Contrast Ratio</i>	400:1
<i>Brightness</i>	300 (nits).
<i>Viewing Angles</i>	120/140 (vertical/horizontal, degrees).
<i>Response Time</i>	8ms typical.
<i>LCD Backlight</i>	LED.
<i>LED Backlight Lifetime</i>	10,000 hours (estimated time to 50% degradation of initial luminous).
<i>Input Signal</i>	Analog RGB, digital

<i>Environmental, Safety</i>	
<i>ESD/EMI/EMC/Safety</i>	UL, CE, FCC.
<i>Operating Temperature</i>	32 ~ 122 -F
<i>Storage Temperature</i>	-40 ~ 158 -F

<i>Ordering Information</i>	
<i>PS/2 keyboard mouse interface</i>	DMK-HD17P
<i>USB keyboard mouse interface</i>	DMK-HD17U