

MPC-1700 Portable Workstation

Rugged Portable Workstation with Slots



Features

- » Custom-build and expandable portable workstation.
- » Aluminum alloy construction.
- » Supports ATX, Micro-ATX form-factor system boards.
- » Supports a single multi-core CPU.
- » Supports PCI, PCI-X and PCI-Express slots for add-on cards.
- » Integrated 17" active matrix flat panel display.
- » Five drive bays: one 5.25" drive bay, two 3.5" drive bays, two slim-line drive bays for optical drive and floppy drive.
- » Integrated keyboard with touchpad pointing device.
- » 650-watt power supply standard, up to 850-watt.

Self-contained Portable Workstation Solution

The MPC-1700 is a portable workstation designed to pack the highest desktop PC performance in a portable package. It comes in a road-ready lunchbox style portable enclosure constructed of aluminum alloy. Protective corner rubber bumpers help to absorb shock during transport, or in the field. It includes a spacious enclosure that supports a Micro-ATX or ATX motherboard, an integrated flat panel display, five drive bays for data storage devices, and expansion slots for add-on cards.

The keyboard folds out for use and includes a touchpad mouse. A 650-watt power supply is standard. A rubber-clad carrying handle makes carrying the system easy, and a luggable carry case with wheels let you transport the system over long distances.

Expandable and upgradable system features

The MPC-1700 offers flexible system configuration using the latest COTS (commercial off-the-shelf) PC components. It packs powerful workstation-class computing capability using the latest multi-core processor technologies by Intel and AMD. The MPC-1700 supports up to three 3.5" hard disk drives in its drive bays. If a RAID configuration is required, it also supports up to six 2.5" hard drives. The MPC-1700 can be configured with an entry-level integrated graphics controller or a high end video card installed in one of its PCI-Express slots.



MPC-1700 Portable Workstation

System Chassis Specifications

System Chassis

<i>Chassis Construction</i>	Portable lunchbox style chassis constructed of aluminum alloy and steel. Integrated flat panel display and fold-out keyboard. Rubber corner bumpers. Tilt-up feet under chassis. Built-in speakers with 2x 6-watt output.
<i>Integrated Display</i>	17" TFT LCD, 1280 x 1024 resolution, 250 cd/m ² , 350:1 contrast ratio.
<i>Storage Bays</i>	2x 5.25" externally accessible drive bays. 1x 3.5" externally accessible drive bay. 1x internal 3.5" drive bay. 1x slim-type optical disk drive bay.
<i>Add-on Card Support</i>	Chassis supports up to seven expansion cards. Number 1 slot* supports expansion card length (length of PCB) up to 8.25" Number 2 ~ 7* slot positions support expansion cards up to 13.3"
<i>Keyboard</i>	Fold-down 108-key keyboard with positive tactile feedback keyswitches. Integrated touchpad pointing device.
<i>Cooling</i>	Two 120mm case fans with filter.
<i>Dimensions</i>	17.5" (W) x 13.5" (H) x 9.5" (D).
<i>Weight</i>	Fully assembled system weighs approximately 35 lbs. Shipping weight: 55 lbs. Actual weight depends on system configuration.

Electrical and Power

<i>Input AC</i>	100 ~ 240 V @ 50 ~ 60 Hz, full range (PFC).
<i>Output</i>	650 watt ATX power supply standard, upgradable to 850 watt power supplies.

Environmental

<i>Temperature</i>	Operating 0~50-C (32~122 -F); non-operating -20~60-C (-4~140 -F)
<i>Humidity (non-condensing)</i>	Operating 20~90% @ 40-C, non-condensing; non-operating 10~95% @ 40-C, non-condensing
<i>Shock</i>	Operating: 10g, 11ms. non-operating: 50g, 11ms.
<i>Vibration</i>	Operating: 20-60Hz, 0.075mm. non-operating: 10-50Hz, 0.15mm
<i>EMI/Safety</i>	Power supply: CE, UL, FCC

Note:

* In most ATX form-factor motherboards, number 1 slot location is usually occupied by a x1 PCI-Express slot. Number 2 ~ 7 slot locations are usually occupied by x16, x8, x4 PCI-Express, or PCI slots. Available slots for add-on cards depends on specific motherboard and system configuration.

MPC-1700 Portable Workstation

Quad-Core CPU System Configuration

System Configuration with Intel Quad-Core Desktop Processor

<i>System Board</i>	Intel Z77 chipset LGA 1155 system board. Supports 4-Channel, dual-port Thunderbolt technology.
<i>Processor</i>	Intel Core i7-3770 Ivy Bridge 3.4GHz quad-core processor with Intel HD Graphics 4000.
<i>System Memory</i>	8GB dual channel DDR3 DRAM installed, up to 32GB.
<i>Graphics Controller</i>	Processor integrated Intel HD Graphics 4000.
<i>Installed Storage</i>	One 320GB 7200 RPM hard drive. One DVD +/- RW optical disk drive.
<i>Storage Device Controller</i>	4x SATA 3.0Gb/s ports. 4 x SATA 6.0Gb/s ports. RAID 0/1/5/10 support.
<i>LAN</i>	Broadcom BCM57781 LAN controller, 10/100/1000Mbps.
<i>Audio</i>	Realtek ALC898 7.1 channels audio controller.
<i>Expansion Slots</i>	2x PCI-E 3.0 x16 slots. 2x PCI-E 3.0 x1 slots. 2x PCI slots.
<i>External Panel I/O Ports</i>	1x PS/2 keyboard/mouse. 1x D-Sub. 1x HDMI. 1x DisplayPort Input for Thunderbolt port (TBT2 for test only). 2x USB 2.0. 4x USB 3.0. 1x eSATA 6Gb/s. 1x S/PDIF Out 5x audio ports.
<i>Operating System</i>	Microsoft Windows 7 Professional 64-bit.

Note

Please use this as a starting point from which components can be modified to meet your application requirements.

MPC-1700 Portable Workstation

Six-Core CPU System Configuration

System Configuration with Intel Six-Core Server Processor

<i>System Board</i>	Intel C602 chipset LGA 2011 system board. Supports Intel Xeon E5-2600/E5-1600 series processors.
<i>Processor</i>	Intel Xeon E5-2630 Sandy Bridge-EP 2.3GHz six-core processor.
<i>System Memory</i>	16GB ECC Registered DDR3 DRAM installed, up to 256GB.
<i>Graphics Controller</i>	Integrated Matrox G200eW with 16MB DDR2 video RAM.
<i>Installed Storage</i>	One Intel 335 Series 240GB SATA III MLC SSD. One 1TB 7200 RPM 32MB Cache SATA 6.0Gb/s hard drive. One DVD +/- RW optical disk drive.
<i>Storage Device Controller</i>	4x SATA 3.0Gb/s. 2 x SATA 6.0Gb/s. RAID 0/1/5/10 support (Windows). RAID 0/1/10 support (Linux).
<i>LAN</i>	Dual 10/100/1000Mbps Ethernet.
<i>Expansion Slots</i>	1x PCI-E 3.0 x16 slot. 1x PCI-E 3.0 x8 (in x16) slot. 1x PCI-E 2.0 x4 (in x16) slot. 3x PCI-X 64bit slots.
<i>External Panel I/O Ports</i>	2x PS/2 ports. 1x COM port. 1x D-Sub VGA port. 2x USB 2.0 ports.
<i>Operating System</i>	Microsoft Windows 7 Professional 64-bit.

Note

Please use this as a starting point from which components can be modified to meet your application requirements.



Contemporary MicroSystems
838 Fairview Ave. Unit J
Arcadia, CA 91007
www.ipctechnology.com
626-487-7034